

ROLFKUHNGBMH

DECLARATION OF PERFORMANCE

for the construction product
Kerafix® 2000

Le/DoP No. 108/01/1806

1. Unique identification code of the product-type:
Kerafix® 2000
2. Type, batch or serial number or any other element allowing identification of the construction product:
order number: see delivery note
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
sealing material for joins in industrial and domestic application
4. Name, registered trade name or registered trade mark and contact address of the manufacturer:
**Rolf Kuhn GmbH
Jägersgrund 10
D-57339 Erndtebrück**
5. If applicable, name and contact address of the authorized representative whose mandate covers the tasks:
not relevant
6. System or systems of assessment and verification of constancy of performance of the construction product:
system 4
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
not relevant

ROLFKUHNGBH

8. In case of the declaration of performance concerning a construction product for which an European Technical Assessment has been issued:

not relevant

9. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction on fire	E	N/A
Composition	Calcium-magnesium-silicate	
Temperature resistance	up to 1200 °C	
Thermal conductivity	0.1 W/mK (400 °C)	


10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

p.p. Marcel Achenbach, Application Engineering
(name and function)

Erndtebrück, 05.06.2018
(place and date of issue)

.....
(signature)



ROLFKUHNGBMH

Kerafix® 2000

**Rolf Kuhn GmbH
Jägersgrund 10
D-57339 Erndtebrück**

18

Le/DoP No. 108/01/1806

sealing material for joins in industrial and domestic application

Kerafix® 2000

Reaction on fire	E
Composition	Calcium-magnesium-silicate
Temperature resistance	up to 1200 °C
Thermal conductivity	0.1 W/mK (400 °C)